

(12) UK Patent Application (19) GB (11) 2 348 907 (13) A

(43) Date of Printing by UK Office 18.10.2000

(21) Application No 0015133.2

(22) Date of Filing 27.05.1998

(30) Priority Data

(31) 133397	(32) 21.11.1997	(33) DK
(31) 1007616	(32) 25.11.1997	(33) NL
(31) 975440	(32) 26.11.1997	(33) NO
(31) 9725153	(32) 27.11.1997	(33) GB

(86) International Application Data
PCT/US98/10735 En 27.05.1998

(87) International Publication Data
WO99/27229 En 03.06.1999

(71) Applicant(s)

BJ Services Company USA
(Incorporated in USA - Delaware)
5500 Northwest Central Drive, Houston, Texas 77092,
United States of America

(72) Inventor(s)

Allan R Rickards
Harold D Brannon

(51) INT CL⁷

E21B 43/26

(52) UK CL (Edition R)

E1F FPA

(56) Documents Cited by ISA

US 4527627 A **US 3888311 A** **US 3659651 A**
US 3481401 A

(58) Field of Search by ISA

US: 166/280,276,278,295,308

(72) cont

Philip J Rae
Gino A Dilullo
Christopher J Stephenson


(74) Agent and/or Address for Service

Forrester Ketley & Co
Forrester House, 52 Bounds Green Road, LONDON,
N11 2EY, United Kingdom

(54) Abstract Title

Formation treatment method using deformable particles

(57) A subterranean formation is treated by injecting a blend of fracture proppant material (20) and a deformable particulate material (10) into the formation. The deformable particulate material (10) may combine with fracture proppant material (20) to increase fracture conductivity, reduce fines generation, and/or reduce proppant flowback. The fracture proppant material may be a material such as sand, and the deformable particulate material may be a material such as polystyrene divinylbenzene beads.



GB 2 348 907 A